


## Technical Specification CCTV

3	Camera IP Dome 2.0 MP	<ul style="list-style-type: none"> <li>• 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition</li> <li>• Outputs max. 2MP (1920 × 1080) @25/30 fps</li> <li>• H.265 codec, high compression rate, ultra-low bit rate</li> <li>• Built-in IR LED, max. IR distance: 30 m</li> <li>• ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments</li> <li>• Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</li> <li>• Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access</li> <li>• Built-in MIC.</li> <li>• 12V DC/PoE power support</li> <li>• IP67 protection</li> </ul>
4	Camera IP Bullet 2.0 MP	<p>2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</p> <p>Outputs max. 2MP (1920 × 1080) @25/30 fps</p> <p>H.265 codec, high compression rate, ultra-low bit rate</p> <p>Built-in efficient IR illuminator, and the max. illumination distance is 30 m</p> <p>ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</p> <p>Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</p> <p>Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access</p> <p>12V DC/PoE power supply</p> <p>IP67 protection</p>
6	POE 8 Port	<ul style="list-style-type: none"> <li>• Intelligent PoE</li> <li>• 8-pin assignment PoE power supply</li> <li>• Long distance PoE</li> <li>• PoE watchdog</li> <li>• Wide working temperature</li> </ul>
7	Cat-6 Cable Cated Copper	<p>UTP CAT6 Cated Cable</p> <ul style="list-style-type: none"> <li>&gt; 305.0 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable</li> <li>&gt; Manufacturing excellence</li> <li>&gt; Customized PVC outer sheath; meet CE CPR Eca flame retardant class certified</li> </ul>

39





	NVR 16 Channel	<ul style="list-style-type: none"> <li>* New 4.0 user interface, Security baseline 2.1</li> <li>* H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch</li> <li>* Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding</li> <li>* Supports mainstream cameras of ONVIF and RTSP protocols</li> <li>* P2P remote surveillance, video play on mobile device</li> <li>* VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K</li> <li>* AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD</li> <li>* Supports remote configuration and management of IPC, such as setting parameters, getting information, and upgrading IPC of the same model in batches</li> </ul>
	Hard Disk Drive 2TB	<ul style="list-style-type: none"> <li>• Capacity: 2TB</li> <li>• Speed: 5,900RPM</li> <li>• Interface Types: SATA</li> <li>• Form Factor: 3.5inx1.0in LFF Hard Drive</li> <li>• Sector Size: 4Kn</li> <li>• Sustained Throughput: 180MB/s</li> <li>• Electrical Interface: SATA 600 - 6.0Gbps</li> <li>On-Board Cache: 64MB</li> </ul>
	Monitor 24 inch	<p>Display Size: 23.8"</p> <p>Resolution: 1920*1080 (60Hz)</p> <p>Panel Type: IPS</p> <p>Contrast: 1000:1</p> <p>Brightness: 250cd/m<sup>2</sup></p> <p>NTSC: 72%</p> <p>Color Support: 16.7M</p> <p>Interface: VGA+HDMI</p> <p>Viewing Angles: 178</p>
	Gigabyte switch 8 Port	<ul style="list-style-type: none"> <li>• Compact design: Miniature size and light weight make it easy to deploy</li> <li>• Plug and play: No configuration required</li> <li>• Green technology: Adopts high quality environmentally friendly plastics</li> <li>7×24H: Stable performance for long-term operation</li> </ul>

③



	4U Network Rack	<ul style="list-style-type: none"><li>Size: 4U (7" high), 19" width, 600mm (24") depth</li><li>Material: Steel, powder-coated finish</li><li>Capacity: 250kg (550 lbs) max load</li><li>Mounting: Adjustable 19" rails</li><li>Cable Management: Cable trays, pass-through</li><li>Security: Lockable front/rear doors</li></ul>
--	-----------------	--

GH

