


Technical Specification CCTV

3	Camera IP Dome 2.0 MP	<ul style="list-style-type: none"> • 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition • Outputs max. 2MP (1920 × 1080) @25/30 fps • H.265 codec, high compression rate, ultra-low bit rate • Built-in IR LED, max. IR distance: 30 m • ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments • Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes • Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access • Built-in MIC. • 12V DC/PoE power support • IP67 protection
4	Camera IP Bullet 2.0 MP	<p>2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition</p> <p>Outputs max. 2MP (1920 × 1080) @25/30 fps</p> <p>H.265 codec, high compression rate, ultra-low bit rate</p> <p>Built-in efficient IR illuminator, and the max. illumination distance is 30 m</p> <p>ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments</p> <p>Rotation mode, DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes</p> <p>Abnormality detection: Motion detection, video tampering, network disconnection, IP conflict, illegal access</p> <p>12V DC/PoE power supply</p> <p>IP67 protection</p>
6	POE 8 Port	<ul style="list-style-type: none"> • Intelligent PoE • 8-pin assignment PoE power supply • Long distance PoE • PoE watchdog • Wide working temperature
7	Cat-6 Cable Cated Copper	<p>UTP CAT6 Cated Cable</p> <p>> 305.0 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable</p> <p>> Manufacturing excellence</p> <p>> Customized PVC outer sheath; meet CE CPR Eca flame retardant class certified</p>



<p>NVR 16 Chancel</p>	<ul style="list-style-type: none"> * New 4.0 user interface, Security baseline 2.1 * H.264, H.265, Smart H.264+, and Smart H.265+. H.265 auto switch * Max. decoding capability: 8 × 1080p@30 fps. Supports adaptive decoding * Supports mainstream cameras of ONVIF and RTSP protocols * P2P remote surveillance, video play on mobile device * VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K * AI by Camera: Face detection, perimeter protection, IVS, people counting, heat map, and SMD * Supports remote configuration and management of IPC, such as set ting parameters, getting information, and upgrading IPC of the same model in batches
<p>Hard Disk Drive 2TB</p>	<ul style="list-style-type: none"> • Capacity: 2TB • Speed: 5,900RPM • Interface Types: SATA • Form Factor: 3.5inx1.0in LFF Hard Drive • Sector Size: 4Kn • Sustained Throughput: 180MB/s • Electrical Interface: SATA 600 - 6.0Gbps On-Board Cache: 64MB
<p>Monitor 24 inch</p>	<p>Display Size: 23.8" Resolution: 1920*1080 (60Hz) Panel Type: IPS Contrast: 1000:1 Brightness: 250cd/m² NTSC: 72% Color Support: 16.7M Interface: VGA+HDMI Viewing Angles: 178</p>

